
Marine Physical Laboratory

Waveguide Invariants and Space-Frequency Time Signal Processing

William A. Kuperman and Gerald D'Spain

Supported by the
Office of Naval Research
Grant N00014-97-D-0350-DO#5

Final Report

January 2002

DISTRIBUTION STATEMENT A
Approved for Public Release
Distribution Unlimited

20040809 088

University of California, San Diego
Scripps Institution of Oceanography

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. Agency Use Only (Leave Blank).		2. Report Date. January 2002		3. Report Type and Dates Covered. Final Report
4. Title and Subtitle. Waveguide Invariants and Space-Frequency Time Signal Processing			5. Funding Numbers. N00014-97-D-0350-DO#5 Project No. Task No.	
6. Author(s). William A. Kuperman and Gerald D'Spain				
7. Performing Monitoring Agency Name(s) and Address(es). University of California, San Diego Marine Physical Laboratory Scripps Institution of Oceanography San Diego, California 92152			8. Performing Organization Report Number.	
9. Sponsoring/Monitoring Agency Name(s) and Address(es). Office of Naval Research Ballston Centre Tower One 800 North Quincy Street Arlington, VA 22217-5660 Scott Tilden, Code 321B			10. Sponsoring/Monitoring Agency Report Number.	
11. Supplementary Notes.				
12a. Distribution/Availability Statement. Approved for public release; distribution is unlimited.			12b. Distribution Code.	
13. Abstract (Maximum 200 words). The objectives of this program were to develop and test new signal processing algorithms based on waveguide invariants for use in three challenging ocean acoustic scenarios: 1) range-dependent environments, 2) signals with low signal-to-noise ratio (SNR), and 3) acoustically cluttered conditions.				
14. Subject Terms. waveguide invariants, shallow water environments, signal processing, hydrophone array			15. Number of Pages. 6	
			16. Price Code.	
17. Security Classification of Report. Unclassified	18. Security Classification of This Page. Unclassified	19. Security Classification of Abstract. Unclassified		20. Limitation of Abstract. None

Waveguide Invariants and Space-Frequency Time Signal Processing

William A. Kuperman and Gerald D'Spain

Supported by the
Office of Naval Research
Grant N00014-97-D-0350-DO#5
for the Period 04/20/99 - 9/30/01

OBJECTIVES

The objectives of this program were to develop and test new signal processing algorithms based on waveguide invariants for use in three challenging ocean acoustic scenarios: 1) range-dependent environments, 2) signals with low signal-to-noise ratio (SNR), and 3) acoustically cluttered conditions.

WORK COMPLETED

- Waveguide invariant-based algorithms that are applicable to range and azimuth varying environments have been developed. These algorithms have been applied to shallow water environments, i.e., ones in which both waveguide boundaries are formed by reflection, and where the range and azimuth dependence is associated with varying ocean bathymetry. The algorithm predictions have been compared with actual shallow water acoustic data from the SWellEx-3 experiment. Results have been published (Publ. 1).
- The CASS/GRAB sonar prediction code has been acquired and installed on the computer system at MPL. An algorithm to calculate the standard waveguide invariant with a ray-based propagation code has

been developed and implemented in a computer code interfaced with CASS/GRAB. The normal mode code Kraken, developed by Mike Porter, also has been modified to calculate the invariant. In addition, a stand-alone program based on a ray theory approach has been created to perform this calculation. The values output from these three codes have been inter-compared and have been compared to analytical expressions in canonical environments. The results have been documented and submitted for publication in the Journal of Underwater Acoustics (Publ. 5). A computer code to calculate the invariant in spatially varying shallow water environments also has been created.

- Invariant techniques have been applied to striation patterns found in broadband ambiguity surfaces from matched field processing. These results are published in Publ. 2. The same approach has been applied to the simpler case of broadband sidelobe behavior in conventional plane wave beam forming.
- Invariant techniques have been used to explain the existence and usefulness of focus regions in single element spectrograms recorded in the deep ocean. Results using data from the Acoustic Thermometry of Ocean Climate (ATOC) program have been published (Publ. 3).
- Striation patterns resulting from application of conventional plane wave beam forming to vertical array data (both simulated data and actual vertical hydrophone array data) for both shallow and deep water environments have been studied from a waveguide invariant point of view. Some results are contained in Publ. 4 and were presented at the Fall, 2000, Acoustical Society of America meeting (Ref. 1).
- Existing data from the SACLANT Centre's 254-m horizontal towed array have been acquired (thanks to Martin Siderius and Tuncay Akal) and data processing has been completed. In addition, we actively participated with Martin Siderius in his experiment with the Centre's towed array in November/December, 2000, and were given 2 days to conduct towed array/broadband source measurements of direct application to this program.
- Interference patterns in towed array beam spectrograms with varying subaperture length have been analyzed to determine the optimal trade-off between physical aperture, synthetic aperture, and array gain.

RESULTS

- Additional data sets of relevance have been acquired and processed to test algorithms developed in this program.

RESULTS

Analytical predictions using the waveguide invariant approach, modified to incorporate range and azimuth dependence in environmental conditions, show very good agreement with striations in single element spectrograms from shallow water acoustic data collected in SWellEx-3 (Publ. 1).

Calculations of the standard waveguide invariant using a stand-alone ray-based code, an algorithm that uses the output from the OAML-approved CASS/GRAB propagation code, and those from the Kraken normal mode code show good agreement, and good agreement with analytical results in canonical environments (Publ. 5).

Sidelobe behavior in broadband ambiguity surfaces from matched field processing can be used to locate underwater sources independent of the main lobe. An analogous result is obtained for estimating the bearing to a source in the simpler case of the broadband sidelobe behavior in conventional plane wave beamforming (Publ. 2).

Focus regions exist in single element spectrograms recorded in the deep ocean that correspond to transitions from one type of propagation to another. These focus regions, along with sound speed information obtained from climatological data bases, can be used to estimate the range to a very-long-distant (Megameter) source (Publ. 3).

The behavior of striations in the vertical wavenumber/range/frequency plane using conventional plane wave beamforming with vertical array data is analytically predicted by an invariant approach in shallow water environments. The striation patterns in the vertical wavenumber/range plane at fixed frequency, as well as in the range/frequency plane at fixed vertical wavenumber, also contain extractable information on source location. For deep water environments, although the striation behavior is more complicated than can be predicted by a strictly invariant approach, some aspects still can be successfully modeled (Publ. 4).

Spectrograms from beams pointed towards a broadband source using both conventional and adaptive plane wave processing with bottom-mounted horizontal array data collected during SWellEx-3 show striation

patterns having the expected array gain and interference cancellation in acoustically cluttered environments. The slope of the interference pattern in the beam spectrograms shows no perceptible distortion from that in the corresponding single element spectrograms in this experimental geometry.

Striation patterns observed in actual ocean acoustic data recorded across the aperture of a horizontal towed array from a broadband source near endfire aft contain robust information on source location in gently range dependent environments. This information can be extracted in an automated way. However, the patterns are significantly degraded when the bathymetry varies strongly spatially.

Analytical expressions that have been derived for the interference patterns measured by acoustic vector sensors and adequately explain their behavior observed in simulation and data.

IMPACT/APPLICATIONS

The waveguide invariant approach has provided a powerful way of examining propagation phenomena in a waveguide. This approach led to novel signal and array processing algorithms. Useful information can be easily extracted from the data from single elements, fixed horizontal bottom line arrays, towed horizontal line arrays, vertical line arrays, and 2D arrays as demonstrated with actual ocean acoustic data.

TRANSITIONS

Transitions have been made, additional transitions presently are in progress, and further transition possibilities are being pursued.

RELATED PROJECTS

1. "Fluctuations and Invariants in Shallow Water," G. L. D'Spain and W. A. Kuperman, sponsored by ONR Code 321 OA. The effects of medium fluctuations on normal mode coupling and the resulting impact on the striation patterns were important issues in both programs.

REFERENCES

2. "Passive Synthetic Aperture Sonar (PasSAS)", MPL's Applied Research Laboratory program, sponsored by ONR Code 321 US. Algorithms and techniques developed in the Waveguide Invariants program are directly applicable to the analysis of the low frequency, broadband data collected in the PasSAS program.
3. "MAPEX2000", Martin Siderius, SACLANT Undersea Research Centre. Data collected by the SACLANTCEN's 254-m horizontal towed array have been used to evaluate algorithms based on waveguide invariants.
4. "Mid-Frequency Ambient Noise Spatial Structure and Implications for Passive Signal Processing", W. S. Hodgkiss, G. L. D'Spain, and W. A. Kuperman, sponsored by ONR Code 321 US. Results of analysis of striation patterns in vertical plane wave beamforming developed in the Waveguide Invariants program are being applied in the MF Noise program.

REFERENCES

1. D'Spain, G. L., Kuperman, W. A., and Murray, J. J. 2000: Source localization using the waveguide invariant approach and conventional plane wave beamforming with vertical hydrophone array data, J. Acoust. Soc. Am. 108 (5), 2646.

PUBLICATIONS

1. D'Spain, G. L. and Kuperman, W. A. 1999: Application of waveguide invariants to analysis of spectrograms from shallow water environments that vary in range and azimuth, J. Acoust. Soc. Am. 106 (5), 2454-2468.
2. Thode, A. M., Kuperman, W. A., D'Spain, G. L., and Hodgkiss, W. S. 2000: Localization using Bartlett matched-field processor sidelobes, J. Acoust. Soc. Am. 107 (1), 278-286.
3. Kuperman, W. A., D'Spain, G. L., and Heaney, K. D. 2001: Long range source localization from single hydrophone spectrograms, J. Acoust. Soc. Am. 109 (5) pt. 1, 1935-1943.

PUBLICATIONS

4. D'Spain, G. L., Kuperman, W. A., and Murray, J. J. 2000: Matchless field processing in shallow water, invited paper, Oceans 2000 MTS/IEEE Conf. Proc., vol. 1, 653-660.
5. D'Spain, G. L., Rovner, G. L., Gerstoft, P., Kuperman, W. A., and Hodgkiss, W. S. 2001: Determination of the waveguide invariant in general environments, submitted to J. Underwater Acoust.

ONR/MPL REPORT DISTRIBUTION

Office of Naval Research (3)
Department of the Navy
Ballston Tower One
800 North Quincy Street
Arlington, VA 22217-5660
Attn: Scott Tilden, Code 321B

Regional Director (1)
ONR Detachment
San Diego Regional Office
4520 Executive Drive, Suite 300
San Diego, CA 92121-3019

Commanding Officer (1)
Naval Research Laboratory
4555 Overlook Avenue, S.W.
Attn: Code 2627
Washington, D.C. 20375-5320

Defense Technical Information Center (4)
8725 John J. Kingman Road
Suite 0944
Ft. Belvoir, VA 22060-6218